


MEGASTAR SYSTEMS OFFICE VERTICAL CAROUSELS ◆ PATHOLOGY UNIT ◆

UNIT DEPTH 36.42" w/o Posting Board	UNIT WIDTH 53.15"	UNIT HEIGHTS 10 carrier 86.61" 12 carrier 100.39" 14 carrier 112.20"	CARRIER (.39" front lip at 45° angle) Clear Width: 38.98" Clear Height: 11.85" Depth: 12.68" Max Load: 330 lbs.
	POSTING BOARD DEPTH 11.8"	POSTING BOARD HEIGHT Clear for seated operation: 29.5" Clear for standing operation: 39.4	SHELF (.39" front lip at 45° angle) Clear Width: 38.50" Clear Height: 3.58" Depth: 12.64" Max Load: 110 lbs.

2 shelves per carrier (allowing for three rows of trays) with 4 supports per shelf and 4 dividers across the top shelf. All dividers must be used, as the shelves have no bottom reinforcement.
Unit supplied with 15 - 12" deep trays per carrier.
Each 3 tier carrier offers 1300 LFI.

Standard Specifications

- Access opening - Seated operation: 29.5"
Standing operation: 39.4"
- Cycle speed - 7.0"/sec
- Stop tolerance - ± 0.59"
- Sound level - 60 dB (approx.)
- Drive - DC gear motor - 1.341 HP (2 speed)
- Power Supply - 110V/20 amps/single phase
- Fuse - 16A delay
- Ambient temperature - Operating: 41° to 122°F Non Operating: -4° to 158°F
- All maintenance from front access panel(s)
- Units can be placed directly side-by-side or back-to-back
- Maximum imbalance load - 660 lbs.
- Top dust cover
- Lockable doors with posting board in seated or standing position
- T-O control housed in movable magnetic matchbox, or recessed in posting board
- Electronics located in the bottom access panel
- Colors - variety of standard packages available
- Emergency service switch
- Expanded error indicator

Quality Features

- Two-year standard warranty on parts and labor
- Remstar products offer full compliance with Americans with Disabilities Act Accessibility Guidelines (ADAAG)

Full Compliance with Americans with Disabilities Act
Accessibility Guidelines (ADA AG)

Safety Features

- Upper and lower safety bars
- Infra-red photocells - 2 sets
- Safety switches for: lower front access panel, handcrank, overheating motor
- Safety factor for drive system 7:1
- Safety status indicator
- Emergency stop buttons

Options (Partial Listing)

- Keyboard and electronics located in overhead position
- Overhead light
- Advanced micro-processor controls
- Adjustable posting board
- Balance meter
- Position lights/indicators
- Custom designer colors
- Optional three-year extended warranty
- Status information panel
- Electronic security access